

# JMC M-7D Desktop Scanner



## JMC M-7D 桌上型二維掃描器 產品特色:

1. 針對零售業作業環境需要設計，縮小機身體積，不佔空間。
2. 支援多種一維條碼二維條碼。
3. USB 介面，模擬鍵盤輸入，隨插即用。
4. 可讀取手機螢幕條碼，適用各種 QR Code 應用。
5. 支援多種作業系統，免安裝驅動程式(XP, Win7~Win10, Linux, Mac)

| Picture Sensor             |                        |                      | 640*480 CMOS                                                                                                                                                                                                                              |                                              |         |
|----------------------------|------------------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|---------|
| Performance Parameters     | Capacity               | 1D                   | EAN-8、EAN-13、EAN-13 2 add-on、EAN-13 5 add-on、ISSN、ISBN、UPC-A、UPC-E、Code11、Code 32、Code 39、Code 93、Code 128、Codabar、Industrial 2 of 5、Interleaved 2 of 5、Matrix 2 of 5、GS1-128、GS1 DataBar（RSS14）、GS1 DataBar Limited、GS1 DataBar Expanded |                                              |         |
|                            |                        | 2D                   | PDF417、MicroPDF417、MicroQR, Data Matrix、QR、Aztec                                                                                                                                                                                          |                                              |         |
|                            | Depth of Field         |                      | Tested Code                                                                                                                                                                                                                               | Minimum                                      | Maximum |
|                            |                        |                      | 5mil code39                                                                                                                                                                                                                               | 1cm                                          | 15cm    |
|                            |                        |                      | UPC 13mil                                                                                                                                                                                                                                 | 1cm                                          | 33cm    |
|                            |                        |                      | 20 mil Code39                                                                                                                                                                                                                             | 1cm                                          | 40cm    |
|                            |                        |                      | 20 mil QR Code                                                                                                                                                                                                                            | 1cm                                          | 28cm    |
|                            | System Compatibility   |                      | Linux 、Android 、Windows XP 、7 、8 、10 、MACOS                                                                                                                                                                                               |                                              |         |
|                            | Decode Accuracy        |                      | Code 39 4mil                                                                                                                                                                                                                              |                                              |         |
|                            | Code Available         |                      | 1D, 2D Codes printing on Paper or film or screen                                                                                                                                                                                          |                                              |         |
|                            | Scan Rate              |                      | 30 Fps                                                                                                                                                                                                                                    |                                              |         |
|                            | Scan Pattern           |                      | Automatic induction continuous scan                                                                                                                                                                                                       |                                              |         |
|                            | Keyboard support       |                      | American-English, French, Italian, German, Spanish, Turkish Q, Belgian (French), English                                                                                                                                                  |                                              |         |
|                            | Barcode output editing |                      | support adding prefix and suffixes, hidden characters                                                                                                                                                                                     |                                              |         |
|                            | Symbol Contrast        |                      | 20%                                                                                                                                                                                                                                       |                                              |         |
|                            | Scanning Angle         |                      | Horizontal : ±70° Vertical: ±60° Rotated: ±360°                                                                                                                                                                                           |                                              |         |
| Human-computer interaction | Indicator light        |                      | Red & Black indicator light                                                                                                                                                                                                               |                                              |         |
|                            | Buzzer                 |                      | Start Tips, Reading code tips                                                                                                                                                                                                             |                                              |         |
| Environment Parameters     | Drop                   |                      | Design to withstand 1.5 M drops to concrete 3 times                                                                                                                                                                                       |                                              |         |
|                            | Environmental Sealing  |                      | IP54                                                                                                                                                                                                                                      |                                              |         |
|                            | Working Temperature    |                      | -20-55℃                                                                                                                                                                                                                                   |                                              |         |
|                            | Conserve Temperature   |                      | -20-60℃                                                                                                                                                                                                                                   |                                              |         |
|                            | Working Humidity       |                      | 5-95% Non-Condensed                                                                                                                                                                                                                       |                                              |         |
|                            | Conserve Humidity      |                      | 5-95% Non-Condensed                                                                                                                                                                                                                       |                                              |         |
|                            | Environment Light      |                      | 0-70000LUX                                                                                                                                                                                                                                |                                              |         |
| Physical Parameters        | Net Weight             |                      | 400g                                                                                                                                                                                                                                      |                                              |         |
|                            | Packing Weight         |                      | 528g                                                                                                                                                                                                                                      |                                              |         |
|                            | Data line length       |                      | 180CM(±3CM)                                                                                                                                                                                                                               |                                              |         |
|                            | Host Size(L*W*H)       |                      | 98.5*98.5*147.3mm                                                                                                                                                                                                                         |                                              |         |
|                            | Packing Size(L*W*H)    |                      | 180mm*168mm*121mm                                                                                                                                                                                                                         |                                              |         |
|                            | Interface              |                      | USB(Drive free)                                                                                                                                                                                                                           |                                              |         |
|                            | working voltage        |                      | 5V                                                                                                                                                                                                                                        |                                              |         |
|                            | USB                    | Standby current      | 133mA/0.665W                                                                                                                                                                                                                              | 正荃科技有限公司                                     |         |
|                            |                        | Working current      | 133mA/0.665w                                                                                                                                                                                                                              | TEL: 02-2918-9661                            |         |
|                            |                        | Working current(Max) | 175mA/0.875W                                                                                                                                                                                                                              | service@correct.com.tw<br>www.correct.com.tw |         |